

FLEXIBLE PHOTOMETERS FOR LAB OR FIELD

YSI's new line of photometers includes the Model 9300 and 9500. Eliminate sample preservation by taking your portable, waterproof instruments to the field to perform the analysis onsite. All reagents are safe and easy to use.

Selecting the desired test has never been easier. Simply navigate among the list of available tests on the screen of the instruments to choose your test and say "OK". The instrument will then walk you through the steps to complete the test. Simple. Convenient. Accurate.

Features (Model 9300 and 9500):

- Direct-reading concentrations with automatic set up
- Waterproof; IP-67 (floats)
- Large backlit graphic display
- Unique sample tube holder accommodates various diameters
- On-screen instructions
- Multiple languages (English, French, German, Spanish, Italian)
- 100+ test choices on the photometer display

Additional Features (Model 9500 only):

- Waterproof USB connection
- Power via USB port
- Internal Memory 500 sample sets
- User-Selectable Options: test units, sample number, dilution factors

Advanced software built into the 9500 instrument remembers the most recent tests, making it even quicker to use the next time. Up to 500 test results are held in the 9500's memory along with a date and time stamp. Simply connect to a PC via USB and drag and drop the files to the PC. Software updates can also be completed through a simple USB connection. In addition, the 9500 allows up to 30 user-defined test methods allowing full flexibility in a range of test methods.



The YSI 9500.

Applications include:

- Aquaculture
- Aquarium management
- Surface water
- Education
- Wastewater
- Watershed management

Specifications

Accuracy $\pm 0.5\%$ at 4% transmittance; ± 0.005 at 0.3 AU

Resolution 0.001 AU

Operating Wavelengths 450, 500, 550, 575, 600 and 650 nm

Display Graphic, backlit LCD with on-screen instructions
Power 3x AA batteries; the 9500 can also be powered via USB

Size (WxLxH) 146 x 275 x 75 mm (5.8 x 10.8 x 3 inches)

Weight 975 g (2 lbs)

Test Cells Automatic adjustment from 12-20 mm diameter



To order, or for more information, contact YSI Environmental.

+1 937 767 7241

800 897 4151 (US) www.ysi.com environmental@ysi.com

YSI Integrated Systems & Services +1 508 748 0366 Fax +1 508 748 2543 systems@ysi.com

SonTek/YSI +1 858 546 8327 Fax +1 858 546 8150 inquiry@sontek.com

YSI Gulf Coast +1 225 753 2650 Fax +1 225 753 8669 environmental@ysi.com

YSI Hydrodata (UK) +44 1462 673 581 Fax +44 1462 673 582 europe@ysi.com

YSI Hydrodata (Ireland) +353 87 2430264 Fax +353 46 673582 ireland@ysi.com

YSI Middle East +973 1753 6222 Fax +973 1753 6333 halsalem@ysi.com

YSI (Hong Kong) Limited +852 2891 8154 Fax +852 2834 0034 hongkong@ysi.com

YSI China +86 10 5203 9675 Fax +86 10 5203 9679 beijing@ysi-china.com

YSI Nanotech (Japan) +81 44 222 0009 Fax +81 44 221 1102 nanotech@ysi.com

ISO 9001 ISO 14001

Pure Data for a Healthy Planet and Who's Minding the Planet? are registered trademarks of YSI Incorporated.

©2007 YSI Incorporated
Printed in USA 1107 W17-04



YSI incorporated Who's Minding the Planet?®

* Includes 30 tests

** Includes YPT285

*** Includes YPT286 and YPT284

Ordering				
Test Kits	Range	Starter Packs (50 Tests)	Replacement Packs (250 Tests)	
Alkalinity, Total (Alkaphot)	0-500 (CaCO ₃)	YPM188	YAP188	
Alkalinity-M (Alkaphot M)	0-500 (CaCO ₃)	YPM250	YAP250	
Alkalinity-P (Alkaphot P)	0-500 (CaCO ₃)	YPM251	YAP251	
Aluminum	0-0.5	YPM166	YAP166	
Ammonia	0-1.0 (N)	YPM152	YAP152	
Boron	0-2.5	YPM190	YAP190	
Bromine	0-10.0	YPM060	YAP060	
Calcium Hardness (Calcicol)	0-500 (CaCO ₂)	YPM252	YAP252	
Chloride (Chloridol)	0-50,000 (NaCl)	YPM268	YAP268	
Chlorine DPD 1	0-5.0	YPM011	YAP011	
Chlorine DPD 2	0-5.0	YPM021	YAP021	
Chlorine DPD 1&3	0-5.0	YPM031	YAPO31	
Chlorine DPD 4	0-5.0	YPM041	YAPO41	
Chlorine HR (High Range)	0-250	YPM162	YAP162	
Chlorine Dioxide (DPD)	0-4.0	YPM052	YAP052	
Chlorine Dioxide LR (Low Range)	0-2.5	YPM064	YAP064	
Chlorine Dioxide HR (High Range)	2.5-20	YPM065	YAP065	
Chromium VI (Hexavalent)	0-1.0	YPM281	YAP281	
Chromium III (Total & Trivalent)	0-1.0	YAT283	N/A	
Copper (Coppercol) (free, combined, total)	0-5.0	YPM186	YAP186	
Copper (free)	0-5.0	N/A	YAP187	
Color (includes turbidity)	10-500	YPM269	N/A	
Cyanuric Acid	0-200	YPM087	YAP087	
Fluoride	0-1.5	YPM179	YAP179	
Hardness (Hardicol)	0-500 (CaCO ₃)	YPM254	YAP254	
Hydrazine	0-0.5	YPM103*	YAP103	
Hydrogen Peroxide LR	0-2	YPM104	YAP104	
Hydrogen Peroxide HR	0-100	YPM105	YAP105	
Iron LR	0-1.0	YPM155	YAP155	
Iron MR	0-5.0	YPM292	YAP292	
Iron HR	0-10	YPM156	YAP156	
Magnesium (Magnecol)	0-100	YPM193	YAP193	
Manganese	0-0.03	YPM173	YAP173	
Molybdate LR	0-20	YPM258	YAP258	
Molybdate HR Nickel	0-100 0-10	YPM175 YPM284	YAP175 YAP284	
Nitrate	0-10 0-20 (N)	YPM163	YAP163	
Nitrite (N)	0-2.5 (N)	YPM109	YAP109	
Nitrite (NaNo ₂)	0-1500 (NaNo ₂)	YPM260	YAP260	
Organophosphonate (OP)	0-20 (PO ₄)	YPM262	YAP262	
Ozone Ozone	0-2.0	YPM056	YAP056	
pH (phenol red)	6.8-8.4	YPM130	YAP130	
Phenol	0-5.0	YPM287	YAP287	
Phosphate LR	0-4.0	YPM177	YAP177	
Phosphate HR	0-100	YPM114	YAP114	
Potassium	0-12	YPM189	YAP189	
Silica	0-4.0	YPM181	YAP181	
Silica HR	0-150	YPM290	YAP290	
Sulphate	0-200	YPM154	YAP154	
Sulphide	0-0.5	YPM168	YAP168	
Sulphite	0-500 (Na ₂ SO ₃)	YPM266	YAP266	
Zinc	0-4.0	YPM148	YAP148	
ltem	Part Number	Description	Description	
9300	YPT9300	9300 photometer	9300 photometer** 9500 photometer***	
9500 285	YPT9500 YPT285	9500 photometer	9500 photometer*** Hard-sided carrying case for the 9300	
286	YPT286	Hard-sided carry	Hard-sided carrying case for the 9500	
804	YPT804	Color Standard k	Color Standard'Kit USB Power Supply for 9500	
283 28 <i>4</i>	YPT283 YPT284	USB Power Suppl USB Waterproof		